ISSN: 3107-6513

# Automated Waste Classification System Using Computer Vision and Deep Learning

Bharathi S, Indumathi SS, Dhanusri M, Bharath Kumar M, Rubadevi G

*Department of Computer Science with Artificial Intelligence and Data Science, KPR College of Arts Science and Research, Coimbatore, Tamil Nadu, India*

## Abstract

This paper presents an automated waste classification system that sorts garbage into four primary groups: recyclable, non-recyclable, hazardous, and organic. Traditional manual segregation methods fail to separate these categories effectively, leading to landfill overflow and environmental contamination. The proposed system uses computer vision and deep learning to detect and classify waste items in real time. Images captured by a digital camera are pre-processed and evaluated by a trained neural network model. By accurately identifying organic materials for composting, recyclables for processing, hazardous waste for safe containment, and non-recyclables for landfills, the system provides a scalable solution for smart waste bins and modern recycling facilities.

***Keywords*—**Waste classification; smart segregation; recyclable materials; hazardous waste; deep learning; automation.

## I. INTRODUCTION

Modern solid waste management demands precise separation at the source to prevent environmental degradation. Discarded trash is composed of diverse materials that require vastly different treatment paths. This work introduces an intelligent framework that automatically classifies incoming waste into four essential streams: organic waste, recyclable waste, hazardous waste, and non-recyclable waste.

Organic waste consists of biodegradable materials such as food scraps and agricultural residues suited for composting. Recyclable waste covers salvageable dry materials including paper, clean cardboard, glass, and certain plastics. Hazardous waste includes toxic or dangerous materials such as electronic components, batteries, and household chemicals that require specialized disposal. Non-recyclable waste comprises multi-layered packaging, contaminated items, and residuals destined for managed landfills. By applying computer vision techniques, this system replaces error-prone human sorting, optimizing the recycling rate while keeping hazardous objects away from domestic municipal streams.

## II. LITERATURE SURVEY

A review of existing literature shows a transition from mechanical sorting to sensor-based and artificial intelligence driven frameworks. Early automated sorting setups used proximity, moisture, and infrared sensors to separate metals from non-metals [1]. While effective for specific materials, these setups struggle to identify varying plastic types or complex geometries.

Recent research relies heavily on support vector machines and early convolutional architectures for classification tasks [2]. Current state-of-the-art systems deploy real-time object detection models such as You Only Look Once (YOLO) [3]. These frameworks process complex visual inputs rapidly, achieving high detection accuracy even when handling overlapping or damaged waste items in messy environments.

## III. BACKGROUND OF THE WASTE MANAGEMENT CRISIS

According to the World Bank urban waste projections and the United Nations Environment Programme global waste management outlook, the volume of municipal solid waste generated worldwide is expanding faster than the rate of urbanization [4]. Global urban waste generation has reached approximately 2.3 billion tonnes annually, with over 30% not managed in an environmentally safe way. This rapid surge has pushed regional infrastructure to its limits, turning city sanitation into an ecological crisis.

The core issue is the lack of source segregation. When consumers dispose of domestic trash, distinct waste categories are co-mingled inside the same collection bins. Combining wet organic fractions with dry recyclables results in severe cross-contamination, ruining tonnes of clean paper, cardboard, and salvageable polymers and rendering them unrecoverable for industrial processing.

## IV. PROBLEM STATEMENT

The primary breakdown in environmental sanitation happens at the point of generation, where waste is thrown into a single container. This lack of source-level segregation compromises subsequent handling and treatment, leading to critical operational challenges.

### *A. Resource Contamination and Degradation*

When organic waste such as high-moisture food scraps and liquid agricultural residues is co-mingled with dry recyclables such as clean paper, corrugated cardboard, and salvageable polymers, cross-contamination occurs immediately. Moisture, grease, and acidic elements from decaying organic items soak into paper fibers and stick to plastic surfaces. This permanently degrades the raw recyclables, making them unusable for industrial recycling and forcing clean materials into landfills.

### *B. Ecosystem Poisoning from Toxic Infiltration*

Due to a lack of visual checkpoints, consumers frequently dump hazardous waste, including lithium-ion batteries, broken electronic components, chemical solvents, and

thermometers, into bins meant for domestic trash. When these items are buried together in general non-recyclable dumpsites, the metallic casing of batteries corrodes over time.

## V. OBJECTIVE OF THE PROJECT

The primary objective is to build an automated, real-time computer vision system that identifies and separates co-mingled garbage into four distinct disposal paths at the source. Using deep learning algorithms, the system routes organic matter for composting, isolates dry recyclables such as plastic and paper for reprocessing, detects hazardous items such as batteries for safe containment, and screens out residual non-recyclable trash destined for landfills.

A core technical milestone is to optimize the software for high detection accuracy and low latency to ensure smooth real-world deployment. The system aims to achieve precise classification that prevents cross-contamination errors even for crushed, crumpled, or overlapping items. By fine-tuning the underlying model layers, the software can process incoming camera frames instantly, making it suitable for integration into automated conveyor belts or smart bin lids.

## VI.SCOPE OF THE PROJECT

The immediate scope is the design and validation of a high-precision software classification module under uniform ambient conditions. The system processes high-resolution images of common consumer garbage and separates them into four target categories: organic food remains, dry recyclable polymers and paper fragments, domestic hazardous electronic waste cells, and residual non-recyclable multi-layered packaging films. By refining the deep learning architecture and building clean training datasets, the software establishes a reliable foundation for real-time computer vision detection.

Looking toward industrial expansion, the scope scales from a digital tracking model to full physical automation. The discrete classification output generated by the Python code can be mapped directly to external microcontrollers via serial communication ports.

## VII. MANUAL WASTE SEGREGATION

Manual waste segregation relies on human labor to identify and separate the components of solid garbage streams on conveyor belts or municipal dumpsites. Although it has been the foundation of municipal sanitation for decades, it struggles to manage growing urban trash volumes and increasingly complex modern packaging. The process is limited by low sorting speed, significant human error, and high operational cost. Because efficiency is tied to the physical speed of human handlers, backlogs of unsorted trash build up during periods of high generation.

Beyond inefficiency, forcing sanitation workers to dig through mixed waste creates severe health and safety risks. Workers are continuously exposed to sharp objects such as glass fragments and medical needles, hazardous household solvents, and toxic airborne fungal spores released by decaying organic waste.

## VIII. AI BASED WASTE SEGREGATION

The automated framework addresses the limitations of manual sorting through a high-speed, contactless computer vision and machine learning architecture. When unsegregated garbage passes through the system, a high-resolution camera captures images of the objects in real time. These images are routed to a trained deep neural network that extracts spatial shapes, surface textures, and color variations, and sorts items into organic scraps, recyclable materials, hazardous electronic waste, or non-recyclable residuals with high confidence and near-zero delay.

By replacing manual hand-sorting with this software loop, the system reduces human error and removes workers from hazardous environments. It handles varying object forms such as crushed plastic bottles, crumpled aluminum cans, and mixed organic residues, avoiding the delays common to older machinery. Because decisions are made at the point of ingestion, clean dry recyclables are separated before wet food scraps can ruin them.

Methodology

## IX. SYSTEM MODULES

The software architecture is a linear pipeline of interconnected modules that handle data from camera capture to final category assignment. The first, the image acquisition module, is the primary hardware-software interface. When waste enters the detection zone, a high-resolution camera captures real-time frames. This module controls exposure and synchronizes lighting to capture crisp frames, which are loaded into memory as multi-dimensional pixel arrays.

The second, the image pre-processing module, cleans the raw pixel arrays for neural network input. Images are resized to standard dimensions such as 416 by 416 or 640 by 640 pixels to match the model input requirements. The module applies adaptive threshold filtering and Gaussian blur to remove background noise, adjusts contrast, and normalizes pixel value distributions. This highlights edges, shape profiles, and textures so the model can identify objects accurately despite messy backgrounds or shadows.

## X. HARDWARE AND SOFTWARE SPECIFICATION

The system relies on an integrated hardware-software architecture to achieve low latency and high detection accuracy. The hardware requires a central processor such as an Intel Core i5 or i7, or alternatively a compact edge-computing platform such as the Raspberry Pi 4 or 5 for low-power smart bin deployments. Visual input is provided by a 1080p USB web camera or a dedicated Pi Camera Module under fixed lighting.

To handle the dense computations of convolutional neural network training, a graphics processing unit such as an NVIDIA GeForce card with CUDA support is used, supported by 8 to 16 GB of system memory and a high-speed solid-state drive for fast image loading and data logging.

The methodology consists of image acquisition, image pre-processing, deep learning based classification, and final category

assignment. Camera images are resized to the required input dimensions, filtered to reduce background noise, and normalized before classification. The system then identifies waste as organic, recyclable, hazardous, or non-recyclable.

## XI. METHODOLOGY

### Results and Discussion

The proposed pipeline is designed for real-time classification and reduces dependence on manual segregation. Its four-category output supports composting of organic waste, recovery of recyclable materials, safe containment of hazardous items, and controlled disposal of residual waste. The current paper describes the system design and intended operation; no numerical accuracy result is reported in the provided content.

## XI. CONCLUSION AND FUTURE SCOPE

This work demonstrates the viability of an intelligent, real-time computer vision system for automating solid waste classification at the source of generation. By analyzing shape profiles, geometric edges, and surface textures, the deep learning architecture reduces human sorting errors and processing delays. The system routes materials into four paths: organic matter for composting, dry recyclables for resource reclamation, hazardous electronic waste for toxic containment, and non-recyclable items for managed landfills. The automated pipeline addresses cross-contamination caused by co-mingled disposal, preserving recyclable polymers and paper before wet organic elements can degrade them.

## REFERENCES

[1] J. Li and J. Zhang, 2022, IEEE journal paper on detecting domestic household trash using smart camera networks.

[2] O. Adedeji and Z. Wang, 2019, study on deep learning and convolutional neural network models for automatic sorting of household garbage.

[3] J. Redmon and A. Farhadi, 2018, research paper on YOLO real-time object detection.

[4] World Bank Group, 2024, global report on solid waste management trends and land pollution forecasts.

[5] S. Sudha and team, 2022, engineering paper on combining computer vision and IoT for waste separation.

[6] M. Rayhan, 2023, comparative analysis of image processing models for multi-class garbage separation.

[7] Central Pollution Control Board (CPCB), 2023, Government of India guidelines on source-level waste segregation.

[8] H. Abdu and M. H. Mohd Noor, "A Survey on Waste Detection and Classification Using Deep Learning," IEEE Access, vol. 10, pp. 128151–128165, 2022, doi: 10.1109/ACCESS.2022.3226682.

[9] I. Joshi, P. Dev, and G. Geetha, "Garbage Classification Using Deep Learning," in Proc. 2023 International Conference on Circuit Power and Computing Technologies (ICCPCT), pp. 809–814, 2023, doi: 10.1109/ICCPCT58313.2023.10245133.

[10] R. Thinakaran, J. Somasekar, V. Neerugatti, and P. Guru Saran, "Automated Waste Classification Using Convolutional Neural Network," in Proc. 2024 14th International Conference on Software Technology and Engineering (ICSTE), 2024, doi: 10.1109/ICSTE63875.2024.00037.

[11] S. Meng and W.-T. Chu, "A Study of Garbage Classification with Convolutional Neural Networks," in Proc. 2020 Indo-Taiwan 2nd International Conference on Computing, Analytics and Networks (Indo-Taiwan ICAN), pp. 152–157, 2020.